

Bunded IBC Store with rear personnel access



Storage Capacity: 8 no. 1000 litre IBCs Shelf Heights: 1300mm

Bunded rear personnel walkway to allow access to IBC outlets.

External Dimensions: L x D x H

5000 x 2850 x 3400mm

Bund: 2200 litre Epoxy coated steel (3.0mm) Bund.

(exceeds 110% and 25% guidelines, ref. EPA). Bund Tested and Certified before dispatch.

Optional Polyethylene Bund for Highly Corrosive Chemicals at extra cost.

Construction: Store delivered to site fully assembled.

Heavy Duty, welded tubular steel framework construction.

Profiled metal wall and roof panels.

Finish: Corrosion resistant, 2 pack polyurethane paint finish.

Epoxy coating on Steel Bunds. PVC Plastisol finish on external walls. Standard Colours: Blue framework RAL 5013, Goosewing grey walls with

merlin grey trim. Other colours possible.

Ventilation: Ventilation louvres on end walls.

Floors/Shelves: Pallets stored on tubular steel Shelf Rails.

Optional removable, galvanised open mesh grating on all shelf levels.

(allows storage of non palletised goods)

Access/Security: Twin Sliding Doors c/w Heavy duty Pad Lock eyes to access IBCs.

Hinged personnel doors to access walkway.

Signage: Hazard / Warning Signs fitted to doors as standard.





Safety Storage Systems

UK: Manchester Business Park, M22 5TG Phone: 0870 0340754

Email: sales@safetystoragesystems.co.uk www.safetystoragesystems.co.uk

IRL: Raheen Ind. Est. Limerick. Phone: 061 225005 Email: sales@safetystorage.ie www.safetystorage.ie