



### Flammables Store Model FS 1.5

Dimensions: 1700w x 1700d x 2500h mm

Storage: 4 x 205 litre drums with 300mm deep shelf above.  
Or can be supplied with shelves - 3 no. storage levels.

Bund: Epoxy coated steel bund.  
Capacity 330 litres. (exceeds EPA & PPG26 requirements).  
Bund integrity tested and issued with bund test certificate.

Construction: High strength welded tubular steel framework. Steel Bund.  
Insulated firewall panels.  
Forklift pockets.  
Suitable for internal or external use.

Fire Protection: **90 minutes Fire protection.**  
Insulated composite Firewall panels tested to BS476 part 22.  
Test Results: Stability and Integrity: 90 minutes.  
Insulation: 90 minutes.

Test Authority: The Loss Prevention Council (LPC) UK.

Four hour fire rating available at extra cost.

Test Results: Stability and Integrity: 240 minutes.  
Insulation: 90 minutes.

Ventilation: One Hour Rated Intumescent ventilation panels fitted at high & low level on side walls. Optional Electrical Extractor.

Finish: Corrosion resistant paint finish.. Plastisol coated external walls.  
Standard colours red steelwork and doors.  
Goosewing grey external walls with merlin grey trim.  
Internal walls white.

Access: Twin hinged fire doors with, lever handles, 5 detainer key operated lock, internal thumb turn and door closer on active leaf.

Signage: Safety/warning signage fitted as standard.  
Wall mounted MSDS holder.

U.L.W. 950kgs.

---



UK: Manchester Business Park, M22 5TG  
Email: [sales@safetystoragesystems.co.uk](mailto:sales@safetystoragesystems.co.uk)

Phone: 0870 0340754  
[www.safetystoragesystems.co.uk](http://www.safetystoragesystems.co.uk)

IRL: Raheen Ind. Est. Limerick.  
Email: [sales@safetystorage.ie](mailto:sales@safetystorage.ie)

Phone: 061 225005  
[www.safetystorage.ie](http://www.safetystorage.ie)