



Flammables Store Model FS 2.0

Dimensions: 2000w x 2000d x 2500h mm

Storage: Option of fixed heavy duty shelving on three walls or steel adjustable shelving.

Bund: 450 litres.(exceeds EPA requirements).

Construction: High strength welded tubular steel framework. Steel Bund.
Insulated firewall panels.
Suitable for internal or external use.

Fire Protection: **One** Hour Rated insulated composite Firewall panels (100mm thick)
tested to BS476 part 22.
Test Results: Stability and Integrity: 60 minutes.
Insulation: 60 minutes.

Test Authority: The Loss Prevention Council (LPC) UK.

Lightweight profiled steel roof designed to vent energy upwards in the event of explosion.

Four hour fire rating available at extra cost.

Four Hour Rated insulated composite Firewall panels (100mm thick)
tested to BS476 part 22.

Test Results: Stability and Integrity: 240 minutes.
Insulation: 60 minutes.

Ventilation: One Hour Rated Intumescent ventilation panels fitted at high & low level on side walls. Optional Electrical Extractor.

Finish: Polyurethane coated steelwork. Plastisol coated external walls.
Standard colours red steelwork and doors.
Goosewing grey external walls with merlin grey trim.
Internal walls white.

Access: Twin hinged fire doors(stainless steel hinges) with 5 detainer key locks and door closers.

Signage: Safety/warning signage fitted as standard.