



(with optional fixed shelving option)

Flammables Store Model FS 2.5

Dimensions: 2500w x 2500d x 2600h mm

Storage: Option of fixed heavy duty shelving on three walls or steel adjustable shelving. See options list.

Bund: 1000 litre epoxy coated steel Bund. (exceeds EPA, PPG26 requirements). Bund integrity tested and issued with bund test certificate.

Construction: High strength welded tubular steel framework.
Insulated firewall panels.
Forklift pockets and roof lifting eyes.
Suitable for internal or external use.

Fire Protection: **90 minute Fire** Rated insulated composite Firewall panels (100mm thick) tested to BS476 part 22.

Test Results: Stability and Integrity: 90 minutes.
Insulation: 90 minutes.

Test Authority: The Loss Prevention Council (LPC) UK.

Lightweight profiled steel roof designed to vent energy upwards in the event of explosion.

Four hour fire rating available at extra cost.

Four Hour Rated insulated composite Firewall panels (100mm thick) tested to BS476 part 22.

Test Results: Stability and Integrity: 240 minutes.
Insulation: 90 minutes.

Ventilation: One Hour Rated Intumescent ventilation panels fitted at high & low level on side walls. Optional Electrical Extractor.

Finish: Corrosion resistant paint finish. Plastisol coated external walls.
Standard colours: red steelwork and doors.
Goosewing grey external walls with merlin grey trim.
Internal walls white.

Access: Twin hinged fire doors with 5 detainer key locks and door closer.

Signage: Safety/warning signage fitted as standard.



UK: Manchester Business Park, M22 5TG
Email: sales@safetystoragesystems.co.uk

Phone: 0870 0340754
www.safetystoragesystems.co.uk

IRL: Raheen Ind. Est. Limerick.
Email: sales@safetystorage.ie

Phone: 061 225005
www.safetystorage.ie