

Internal Gas Cylinder Cabinets - 90 minute Fire rated.



- High quality Cabinets with high levels of Fire Protection in accordance with the new European Safety Standard EN 14470-1(replaces DIN 12925-1)
- These cabinets have been subjected to a time/temperature test(BS EN 1363-1), to determine how long the inner temperature takes to reach 180°C
- Fully Insulated Construction
- 100mm Air inlet and Outlet in rear panel – seals itself in the event of fire(automatically at 70°C)
- Self Closing Doors(automatically close if external temperature reaches 50°C).
- Key operated Locks on each door
- Door seals expand in the event of fire to fully seal cabinet.
- Spill Containment Sump(maintains its integrity after fire test).
- Access ports/holes in roof(outer skin pre drilled) for pipelines.
- Fixing rails for manifolds.

90 Minute Fire Protection

Model 794BG	<u>Capacity</u> 2 (B50 cylinders)
Dims: Ext: 705w x 615d x 2075h mm. Int: 565w x 530d x 1855h mm	
Horizontal C-rail for fixing gas cylinders	
Access Ramp	

Model 795BG	4 (B50 cylinders)
Dims: Ext: 1260w x 615d x 2075h mm. Int: 1120w x 530d x 1855h mm	
Horizontal C-rail for fixing gas cylinders	
Access Ramp	



UK: Manchester Business Park, M22 5TG
Email: sales@safetystoragesystems.co.uk

Phone: 0870 0340754
www.safetystoragesystems.co.uk

IRL: Raheen Ind. Est. Limerick.
Email: sales@safetystorage.ie

Phone: 061 225005
www.safetystorage.ie